

**PDFN5X6-8L P Channel Enhancement 沟道增强型
MOS Field Effect Transistor 场效应管**

■ Features 特点

Low on-resistance 低导通电阻

$R_{DS(ON)}=5.7m\Omega(\text{Type})@V_{GS}=-10V$

$R_{DS(ON)}=8.5m\Omega(\text{Type})@V_{GS}=-4.5V$


■ Applications 应用

Load Switch 负载开关

PWM Application 脉宽调制

Power Management 电源管理

■ Internal Schematic Diagram 内部结构



■ Absolute Maximum Ratings 最大额定值

Characteristic 特性参数	Symbol 符号	Rat 额定值	Unit 单位
Drain-Source Voltage 漏极-源极电压	BV_{DSS}	-30	V
Gate- Source Voltage 栅极-源极电压	V_{GS}	± 20	V
Drain Current (continuous)漏极电流-连续	I_D (at $T_C = 25^\circ\text{C}$ at $T_A = 25^\circ\text{C}$)	-50 -20	A
Drain Current (pulsed)漏极电流-脉冲	I_{DM}	-100	A
Total Device Dissipation 总耗散功率	$P_{TOT}(\text{at } T_C/T_A = 25^\circ\text{C})$	29.8/2.3	W
Avalanche Energy(Single Pulse)雪崩能量	E_{AS}	49	mJ
Thermal Resistance Junction-Ambient 热阻	$R_{\theta JA}$	55	$^\circ\text{C}/\text{W}$
Junction/Storage Temperature 结温/储存温度	T_J, T_{stg}	-55~150	$^\circ\text{C}$

■ **Electrical Characteristics 电特性**

($T_A=25^{\circ}\text{C}$ unless otherwise noted 如无特殊说明, 温度为 25°C)

Characteristic 特性参数	Symbol 符号	Min 最小值	Typ 典型值	Max 最大值	Unit 单位
Drain-Source Breakdown Voltage 漏极-源极击穿电压($I_D = -250\mu\text{A}, V_{GS}=0\text{V}$)	BV_{DSS}	-30	—	—	V
Gate Threshold Voltage 栅极开启电压($I_D = -250\mu\text{A}, V_{GS} = V_{DS}$)	$V_{GS(th)}$	-1.3	-1.8	-2.3	V
Zero Gate Voltage Drain Current 零栅压漏极电流($V_{GS}=0\text{V}, V_{DS}= -24\text{V}$)	I_{DSS}	—	—	-1	μA
Gate Body Leakage 栅极漏电流($V_{GS}=\pm 20\text{V}, V_{DS}=0\text{V}$)	I_{GSS}	—	—	± 100	nA
Static Drain-Source On-State Resistance 静态漏源导通电阻($I_D = -20\text{A}, V_{GS} = -10\text{V}$) ($I_D = -20\text{A}, V_{GS} = -4.5\text{V}$)	$R_{DS(ON)}$	—	5.7 8.5	7 12	$\text{m}\Omega$
Diode Forward Voltage Drop 内附二极管正向压降($I_{SD} = -1\text{A}, V_{GS}=0\text{V}$)	V_{SD}	—	-0.7	-1	V
Input Capacitance 输入电容 ($V_{GS}=0\text{V}, V_{DS}= -15\text{V}, f=1\text{MHz}$)	C_{ISS}	—	2830	—	pF
Common Source Output Capacitance 共源输出电容($V_{GS}=0\text{V}, V_{DS}= -15\text{V}, f=1\text{MHz}$)	C_{OSS}	—	430	—	pF
Reverse Transfer Capacitance 反馈电容 ($V_{GS}=0\text{V}, V_{DS}= -15\text{V}, f=1\text{MHz}$)	C_{RSS}	—	365	—	pF
Total Gate Charge 栅极电荷密度 ($V_{DS}= -15\text{V}, I_D = -20\text{A}, V_{GS} = -10\text{V}$)	Q_g	—	50	—	nC
Gate Source Charge 栅源电荷密度 ($V_{DS}= -15\text{V}, I_D = -20\text{A}, V_{GS} = -10\text{V}$)	Q_{gs}	—	9	—	nC
Gate Drain Charge 栅漏电荷密度 ($V_{DS}= -15\text{V}, I_D = -20\text{A}, V_{GS} = -10\text{V}$)	Q_{gd}	—	12	—	nC
Turn-ON Delay Time 开启延迟时间 ($V_{DS}= -15\text{V}, I_D = -1\text{A}, R_{GEN}=3\Omega, V_{GS} = -10\text{V}$)	$t_{d(on)}$	—	13	—	ns
Turn-ON Rise Time 开启上升时间 ($V_{DS}= -15\text{V}, I_D = -1\text{A}, R_{GEN}=3\Omega, V_{GS} = -10\text{V}$)	t_r	—	18	—	ns
Turn-OFF Delay Time 关断延迟时间 ($V_{DS}= -15\text{V}, I_D = -1\text{A}, R_{GEN}=3\Omega, V_{GS} = -10\text{V}$)	$t_{d(off)}$	—	125	—	ns
Turn-OFF Fall Time 关断下降时间 ($V_{DS}= -15\text{V}, I_D = -1\text{A}, R_{GEN}=3\Omega, V_{GS} = -10\text{V}$)	t_f	—	66	—	ns

■ Typical Characteristic Curve 典型特性曲线




Figure 1: Output Characteristics




Figure 2: Transfer Characteristics




Figure 3: Diode Characteristics




Figure 4: On-Resistance vs. Drain Current




Figure 5: Capacitance Characteristics




Figure 6: Gate-Charge Characteristics

■ Typical Characteristic Curve 典型特性曲线




Figure 7: On-Resistance vs. Tj




Figure 8: On-Resistance vs. VGS




Figure 9: Drain Current Characteristics




Figure 10: Safe Operating Area




Figure 11: Transient Thermal Response Curve

■ Dimension 外形封装尺寸

